

## EPS® 2252

### Acrylic Emulsion

**MARKET SEGMENT: CONSTRUCTION**

**COMMON APPLICATIONS: PRIMER, BASECOAT**

EPS® 2252 is a high solids acrylic emulsion designed to adhere to low-energy substrates commonly used in roofing. Basecoats and primers based on EPS 2252 offer outstanding adhesion to thermoplastic olefin (TPO) and ethylene propylene diene monomer (EPDM) rubber. EPS® 2252 provides the capability to formulate coatings at <50g/L VOC.

#### PERFORMANCE BENEFITS

- Excellent adhesion to TPO, EPDM, metal, asphalt, and other common roofing substrates
- <50 g/L VOC capable
- Can be used in both primer and basecoat formulations
- Made without APEO surfactants

#### TYPICAL PROPERTIES

|                      |                |
|----------------------|----------------|
| <b>Weight Solids</b> | 60.0 +/- 0.70% |
| <b>Weight/Gallon</b> | 8.55 +/- 0.10  |
| <b>pH</b>            | 8.0 - 9.0      |
| <b>Volume Solids</b> | 59.0 +/- 0.70% |
| <b>Tg</b>            | -32° C         |

These typical properties do not represent specifications.

#### SUGGESTED FORMULATIONS

- EPS® 2252 RC1 – Roof Coating Basecoat