

## EPS® 2257

### All-Acrylic Emulsion

**MARKET SEGMENT: CONSTRUCTION**

**COMMON APPLICATIONS: SEALER**

EPS® 2257 is an all-acrylic emulsion offering excellent penetration, adhesion and water resistance on cementitious substrates.

#### PERFORMANCE BENEFITS

- Provides the capability to formulate coatings at <100g/L VOC
- Blush and water resistance
- Rapid hardness development
- UV and yellowing resistance
- Made without APEO surfactants

#### TYPICAL PROPERTIES

<b>Weight Solids</b>	40.0 ± 0.7%
<b>Weight/Gallon</b>	8.80 ± 0.10
<b>pH</b>	8.0 – 9.0
<b>Volume Solids</b>	36.5 ± 0.7%
<b>MFFT</b>	7° C
<b>Volatile(s)</b>	Water

These typical properties do not represent specifications.

#### SUGGESTED COALESCING SOVENT(S)

**(% Solvent on Binder Solids – Pass 40°F LTC Test)**

<b>Texanol</b>	5%
----------------	----

#### SUGGESTED FORMULATIONS

- EPS® 2257 S1 - Low VOC Concrete Sealer (20% solids)
- EPS® 2257 ST1- Low VOC Concrete Stain (15% solids)