

TECHNICAL DATA SHEET

RayCryl[®] 1837

ALL-ACRYLIC EMULSION

MARKET SEGMENTS: Specialty - Textile

RayCryl[®] 1837 is a hard and stiff all-acrylic emulsion designed for use as a domestic and industrial textile fabric coating.

PROPERTIES:

- Self-crosslinking and carboxyl group
- Stiff free film
- Accepts high filler loading and flame retardants
- UV resistance
- Made without APE-containing surfactants
- Low VOC capabilities

COMMON APPLICATIONS: Industrial fabric coating

Specifications

Weight Solids	50%
Weight/Gallon	8.6
pH	3.5 - 4.5

Typical Properties

T _g	41°C
----------------	------

Questions? Call EPS Customer Service @ 1-800-654-4242 / Email: info@eps-materials.com

1/5/2023

TECHNICAL SUPPORT: These guidelines are offered to assist the paint formulator in achieving the high performance properties noted and are offered for illustration purposes only; the paint formulator bears sole responsibility for the performance of the final coating product.

SDS: For details on health, safety and handling information, Safety Data Sheets (SDS) are available at www.epscca.com.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. Unless otherwise agreed in writing, all sales of EPS products are governed by the EPS Terms and Conditions of Sale, available at <https://www.epscca.com/galleries/pdfs/salesterms.pdf>.